



- NOTES:
1. OUTPUT: 11.7 uW/CM2 PER LINEAR INCH OF ARC LENGTH @ 1 METER (45 DEG F, 400 FPM)
 2. STAINLESS STEEL CONSTRUCTION.
 3. SEE CHART FOR REPLACEMENT LAMP AND BALLAST PART NUMBERS.
 4. FIXTURE MODELS ARE SPECIFIC FOR 120 OR 230 VAC 50/60 Hz OPERATION.
 5. SEE SHEET 2 OF 3 FOR 277 VAC 50/60 Hz MODELS.
 6. SEE SHEET 3 OF 3 FOR 120-230 VAC JUNCTION BOX DETAILS.
 7. UL CLASSIFIED STANDARD 1995.

CC SERIES HIGH OUTPUT DUAL LAMP UTILITY FIXTURES										
MODEL NUMBER	PART NUMBER	VOLTAGE	AMP DRAW	(A) LENGTH	(B) LENGTH	(C)	(D)	REPLACEMENT LAMP	REPLACEMENT BALLAST	WEIGHT
CC18-2-120	2540-01	120	0.50	18.00"	15.19"	6.00	6.00	GCL-010	TXG270	5.00 lbs
CC18-2-230	2540-02	230	0.30	18.00"	15.19"	6.00	6.00	GCL-010	TXG275	5.00 lbs
CC24-2-120	2540-04	120	1.15	24.00"	21.19"	5.50	13.00	GCL-020	TXG270	6.50lbs.
CC24-2-230	2540-05	230	0.70	24.00"	21.19"	5.50	13.00	GCL-020	TXG275	6.50 lbs
CC36-2-120	2540-07	120	1.60	36.00"	33.19"	6.00	24.00	GCL-030	TXG270	8.25 lbs.
CC36-2-230	2540-08	230	0.80	36.00"	33.19"	6.00	24.00	GCL-030	TXG275	8.25 lbs.
CC48-2-120	2540-10	120	2.30	48.00"	45.19"	8.00	32.00	GCL-040	TXG270	10.00 lbs
CC48-2-230	2540-11	230	1.20	48.00"	45.19"	8.00	32.00	GCL-040	TXG275	10.00 lbs
CC60-2-120	2540-13	120	3.00	60.00"	57.19"	8.00	44.00	GCL-050	TXG270	13.25 lbs.
CC60-2-230	2540-14	230	1.60	60.00"	57.19"	8.00	44.00	GCL-050	TXG275	13.25 lbs.

American Air & Water, Inc.
 888-378-4892 * Fax 843-785-2064

DATE: 6/1/2007
 CC SERIES DUAL LAMP FIXTURES FOR HVAC

1 OF 4 AUV-2540A